



## مشخصات فنی توری فایبر گلاس

| CURRENT PRODUCT NAME : MASTER A 20 |                                    |  |
|------------------------------------|------------------------------------|--|
| 1                                  | CODE                               | 75-5×5   |
| 2                                  | WEAVE                              | TWILL  |
| 3                                  | YARN<br>(tex)                      | WARP<br>WEFT<br>67×2<br>200  |
| 4                                  | DENISTY<br>COUNT/25mm              | WARP<br>WEFT<br>9<br>7   |
| 5                                  | MESH SIZE(MM)                      | WARP<br>WEFT<br>1,3<br>3   |
| 6                                  | FINISHED WEIGHT(g/m <sup>2</sup> ) | 75( ± 5)   |
| 7                                  | TENSILE<br>STRENGTH<br>N/5cmx20cm  | WARP<br>WEFT<br>780<br>780   |
| 8                                  | WOVEN STRUCTURE                    | LENO   |
| 9                                  | COUNTENT OF RESIN %(>=)            | 15   |
| 10                                 | ROLL SIZE                          | 0.2 m × 50 m   |
| 11                                 | STANDARD COLOR                     | WHITE  |
| 12                                 | THREAD MARKING                     | 3 LINES THREADS AT ONE EDGE  |
| 13                                 | MAIN FIELDS OF<br>APPLICATION      | 1.Wall reinforce<br>2.Out-side wall heat insulation<br>3.Roof waterproof<br>4.Reinforcement,marble,mosaic,bitumen,plaster,etc. |
| 14                                 | PACKING                            | 20 ROLLS/CARTON  |

### Storage:

Keep mesh from prolonged exposure to weather.

Do not allow petroleum products come into contact with mesh.

### Shelf life:

Two(2) years or more when properly stored in unopened packages.